#3

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Commissioner of Patents and Trademarks, Washington, D.C. 20231 on

6.12.01
(Date of Deposit)

Signature 6/12/01 (Date of Signature)

OIPE JC12 JUN 15 2001 PATENT & TRADEMARK OFFICE

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of	:
Richard D. Baertsch et al.	:
Serial No.: 09/774,530	: Group Art Unit: 2878
Filed: January 31, 2001	: Examiner:
For: DETECTOR FRAMING NODE ARCHITECTURE TO COMMUNICATE IMAGE DATA	: Attn: Official Draftsman : Allowed Date: : Issue Batch No.

To the Assistant Commissioner for Patents

TRANSMITTAL OF FORMAL DRAWINGS

Enclosed please find 53 sheet(s) of formal drawings for the above-identified patent application.

Respectfully submitted,

John F. Thompson
Reg. No. 43,953
Telephone: (518) 387-6275
Or (518) 387-7122

Schenectady, New York

Date June 11, 2001


RADIATION GENERATION SYSTEM
109
102
X-RAY CONTROL SYSTEM
110
100
114
HOST COMPUTER
119
MONITOR
104
106
HOST PROCESSOR
115
HOST MEMORY
117
108
116
112
FLAT PANEL DETECTOR
POWER SUPPLY/ CHILLER
118
IMAGE DETECTION SYSTEM
DETECTOR FRAMING NODE
304

fig. 1



fig. 2

(PRIOR ART)

T03030 DES42262



fig. 3

FOSGB: DESI2260



fig. 4
(Prior Art)



fig. 5
(Prior Art)



fig. 6
(PRIOR ART)



fig. 7
(PRIOR ART)



CARDIAC/SURGICAL DIGITAL X-RAY PANEL

fig. 8

(PRIOR ART)



fig. 9 (PRIOR ART)



fig. 10

(PRIOR ART)



RADIOGRAPHY DIGITAL X-RAY PANEL

fig. 11 (PRIOR ART)



fig. 12
(PRIOR ART)



MAMMOGRAPHY DIGITAL X-RAY PANEL

fig. 13

(PRIOR ART)



fig. 14
(PRIOR ART)


114
Script
309
User App.
301
Frame Sequence
310
Event Sequence
312
Disk Archive
308
Test Calculation Unit
320
318
Gain, offset, bad pixel correction unit
311
Test Control Unit
Image Data
316
Acquisition DLL
313
DFN Devise Driver
314
Host Computer
300
Computer Communication Bus
302
304
Detector Framing Node
322
Event Queue
Acquistion Control Unit
324
Frame Store
325
379
377
Radiation Generation System 109
Image Detection System 112

fig. 15


339
Excel User Interface
331
Translator
330
User API
335
Display Library
336
Image Process Library
337
Archive Library
328
338
High Res. Display
333
Perl Script Unit
Acquisition DLL
313
408
Event Simulator
Event Compiler
DFN Device Driver
314
308
Disk Archive
407
302
109
329
Binary File Unit
Detector Framing Node
Radiation Generation System
304
377
112
Image Detection System
Software system for real time radioscopic imaging

fig. 16

fig. 17



Hardware system for real time radioscopic imaging


DFN Memory Unit
Frame Buffer Memory Unit
Frame Buffer Memory Unit
Frame Buffer Memory Unit
Frame Buffer Memory Unit
Frame Buffer Memory Unit
381
380
370
372
Data Acquisition Processor
386
L Bus test Connector
390
304
F.O. Test Connector
388
DAP-EP test Connector
376
374
Image Detection System 112
Image Detection Interface
Event Processor
377
384
378
Real Time Bus Interface
DFN Control Unit
Radiation Generation System 109
Computer Communication Interface
382
379
Detector Framing Node
302
Host Computer 114

fig. 18

		(fm/sec)	length	latency	memory	offset	gbr
Panel Setup	Real Time	30	unlimited	<5 frames	host	none	
Single Frame	Post Process	-	-	Delay ~.1 sec	"	y	
Single Frame	Post Process	-	-	Delay ~.2 sec	"	y	y
Real Time	Real Time	R	unlimited	<5 frames	host	none	
Real Time	Real Time	R-X	unlimited	<5 frames	"	y	
Real Time	Real Time	R-Y	unlimited	<5 frames	"	y	y

fig. 19

Modality	image size	Frames Stored host memory
Cardiac	1024 X 1024	200
Rad	2048 X 2048	50
Mammo	2304 X 2048	44

fig. 20


Tester Application
402
400
404
406
414
416
Config Files
Sequence Files
Calibration Files
412
Batch Process Interface
Programming Interface Library
337
339
Hardware Drivers Library
Tester Resources
418
Aquisition Hardware

fig. 21


301
User Interface
408
Event Compiler
409
Hardware Debug Toolkit
411
External Device 0 support (DFN)
External Device 1 support (DFN)
410
External Device support
Bus Interface
Hardware Drivers Interface
413
304
Detector Framing Node
379
377
109
Radiation Generation System
112
Image Detection System
117
Host Memory
338
High Resolution Display

fig. 22


Frame timing
Frames before expose
Frames during expose
Frames after expose
Frame interval
Exposure Time Delay
Frame setup time
Scan Voltages
Common Voltage (1&2)
Compensation Voltage
Reference Voltage
Row Off Voltage
Row On Voltage
Scan Setup Parameters
Ramp select (0-15)
Timing mode (0-7)
ARC Bandwidth
ARC Feedback Cap (0-3)
ARC Gain (0-3)
Rows readout (1,2,16,32)
Row enable
Row Long/Short
Compensation enable
Compensation Lng/Shrt
Right Row T/S
Left Row T/S
Digital Test Select (0-7)
Analog Test Select (0-7)
Analog Test Src (0-15)
Common Voltage Select
DRC Column Sum
SETTINGS OF DETECTOR CONTROL BOARD CONTROLLED BY DFN 304

fig. 23



fig. 24


Detector Control Board 124
480
482
492
374
Fibre Channel Interface
EP FC Control Unit
EP FC TX Unit
EP FC RX Unit
Event Processor
GCLK1
GCLK2
Reset1
Reset2
Reset3
494
484
486
496
472
470
Event Sequencer UNIT
Queue Control Unit
EAB Memory
Event Queue 322
Event Interpreter
Real Time Bus 379
EP Real Time Bus Interface
474
476
490
EP Control Unit
452
PCI/Local Bus Interface Unit
PCI Command Interpreter
462
460
454
450
Error Registers
Control Registers
456
Master Control Unit
464
Local Bus Interface
Local Bus 384

fig. 25


Image Detection Bus 377
Data Acquisition Processor
372
516
518
GCLK1
GCLK2
Reset1
Reset2
Reset3
520
DAP FC Rx Unit
500
DAP FIFO Unit
502
Pixel Reorder Unit
504
DFN Memory Unit
380
Crossbar
506
DAP Control Unit
522
Error Registers
524
Control Registers
521
Master Control Unit
526
Ram Bist
528
Image Frame Controller
508
514
Read /Write Cycle Controle Unit
510
Line Reorder Unit
Address Generator
507
509
Local Bus Arbitrator
Local Bus Interface
512
Local Bus 384

fig. 26


370
535
Vcc
Vcc
534
EP
POR
Unit
Power On
Reset Unit
Vcc
536
DAP
POR
Unit
374
Event
Processor
529
Programmable
Memory Unit
EP
EEPROM
Unit
530
532
DAP
Eeprom
Unit
372
Data
Acquisition
Processor
541
DFN Control Unit
545
542
JTAG1
544
JTAG2

fig. 27



fig. 28



fig. 29



fig. 30



fig. 31



fig. 32



fig. 33



fig. 34



fig. 35



fig. 36


382
LBA(31:0)
LBD(31:0)
Local Bus
384
LB_CNTL (15:0)
AD(31:0)
CBE(3:0)
Computer
Communication
Bus 302
PCI_CNTL (15:0)
Computer Communication Interface

fig. 37


Sig_Det
376
568
566
562
Tx_ cntl
3
10
FO Tran. Unit
2
Tx_ data
32
560
Encoder/ Decoder Unit
F. O. Transceiver
Image Detection Bus 377
Rx_ data
32
Rx_ cntl
12
10
FO Rec. Unit
2
564
Image Detection Interface
COMPUTER COMMUNICATION Bus 302

fig. 38



fig. 39



fig. 40



fig. 41



fig. 42


574
Local Clock
576
Clk Buffer
PCI Clock 587
F.C. Receive Clock 585
582
F.C. Tran. Clock
584
Clk Buffer
576
5
Computer Communi-cation Interface
382
Event Processor
374
Data Acquisition Processor
372
DFN Memory Unit
380
Image Detection Interface
376
Local Bus Test Port
577

fig. 43


MON
OB1
OB2
OB3
OB4
OB5
INB
OEB
OA1
OA2
OA3
OA4
OA5
INA
OEA
Clock Buffer
576

fig. 44


DFN Control Unit
Data Acquisition Processor
DAP Config_done
EP Config_done
580
DAP Config_done
Vcc
535
382
372
374
PCI Data
Computer Communication Interface
LCL Reset
POR Unit
Event Processor
EP Config_done
PCI Reset
User 0
370
606
Image Detection Interface
376
PCI EEMPROM
588

fig. 45


590
378
F.C. Test Port
DAP/EP/Test Port
602
Serial Interface Chip
Serial Interface Chip
Serial Interface Chip
Serial Interface Chip
604
RTB
606
PCI EEPROM
610
614
542
544
566
Encoder/ Decoder Unit
F.O. Tran Unit
562
600
SRAM Chip
SRAM Chip
SRAM Chip
SRAM Chip
SRAM Chip
SRAM Chip
592
EEPROM Chip
530
EEPROM Chip
594
612
Local Bus Test Port
374
372
596
EEPROM Chip
532
EEPROM Chip
598
376
564
382
Image Detection Interface
F.O.Rec Unit
Computer Communication Interface
Event Processor
Data Acquisition Processor
304

fig. 46



Mapping of 16 MByte PCI Address Space

fig. 47

fig. 48


630
BIST
BIST_CMP
632
DIAGNOSTIC
GO_TEST
GO_DIAGNOSTIC
GO_DIAGNOSTIC
GO_NORMAL
634
TEST
NORMAL
638
START_QUEUE
END_QUEUE
START_QUEUE
END_QUEUE
RUN_T
RUN
636
640
Restart_DFN
Disable_Function
Switch_RL_Buffer
Go_Test
Go_Normal
Get_Status
Run_Bist
Abort_DMA
Setup_DMA
Read_Local_Bus
Send Command
Fc_RCV_Snapshot
Generate_Error
Unimplemented
Restart_DFN
Disable_Function
Switch_RL_Buffer
Go_Diagnostic
Write_EAB
Read_EAB
Start_Queue
Generate_Error
Unimplemented
Restart_DFN
Switch_RL_Buffer
Write_EAB
Read_EAB
Abort_Queue
Generate_Error
Unimplemented

T0330 "0E3T4260



fig. 49

Event Mnemonic	***Event*** (showing size of arguments)	***Op Code*** (hex)	***Data*** (bytes)	***Total*** (bytes)
Endq	Endq	14	0	1
Delay (T)	Delay (0xff ff ff ff)	10	4	5
Send (command, value)	Send (0xff ff ff ff, 0xff ff ff ff)	04	8	9
LoopKN (K, N)	LoopKN (0xff ff, 0xff)	0C	3	4
LoopKF (K, F)	LoopKF (0xff ff, 0xff ff ff)	0D	5	6
Wait (F)	Wait (0xff ff, ff)	09	3	4
Flag (F)	Flag (0xff ff, ff)	08	3	4

660

fig. 50

fig. 51



Error Mnemonic	Description of Error
FC_TIMEOUT	Timeout Expired With No ACK Detected
FC_BAD_ACK	ACK Did Not Match Transmitted Command
FC_EXTRA_ACK	Unexpected ACK Received
FC_EXTRA_CMD	New Send Event While Waiting for ACK From Previous Send
SIG_DETN	No Input Signal Power on Fibre Channel (Cable Disconnected?)
RXERROR	Fibre Channel Receiver Detected Bad Data (Defective Chipset?)
WRDSYNCN	Fibre Channel Data Link Unsynchronized
CRXS(1)	Bad Received CRC Detected (Fiber-optic Cable Problem?)
CRXS(3) & CRXS(2)	Bad Order in Link State Machine (Defective Chipset?)

672

fig. 52



fig. 53



fig. 54

TOSCO1 DESI2686



fig. 55



fig. 56



fig. 57



fig. 58

PCT/EP98/08200



fig. 59

E11	EndQ
E10	Delay 125 ms
E9	Send Im Request
E8	Delay 500 ms
E7	Flag RT2
E6	Delay 50 ms
E5	Delay 125 ms
E4	Send Im Request
E3	Delay 300 ms
E2	Loop 2, RT1
E1	Send Scrub
E0	Delay 300 ms



EVENT QUEUE

fig. 60


Normal Mode
Run Mode
702
Normal Mode
Beat1
Beat2
Beat3
xon
xon
xon
E0
E2 E4 E6
E1 E3 E5 E7
E8
Wait F
Wait For Beat

fig. 61


EndQ
E7
LoopKF, HF1
E6
Delay 23 ms
E5
Send Im Request
E4
Delay 10 ms
E3
Flag RT2
E2
Delay 23 ms
E1
Send Scrub Request
E0
Wait RT1
704
EVENT QUEUE

fig. 62


CONSTANT DATA
Offset 0..15
Gain Integer 0..15
Gain Fraction 0..15
Offset 16..31
Gain Integer 16-31
Gain Fraction 16-31
Constant Memory Format

fig. 70


Normal Mode
Run Mode
Normal Mode
End Q
Auto Scrub
Auto Scrub
Auto Scrub
Scrub
Dark Image
Light Image
Scrub
Auto Scrub
Auto Scrub
Auto Delay
Begin Sequence Received

fig. 63

```
sequence_begin ( );
# define qv defaults:
%qv1 =('delay_qv' => 5000);
# call frame with qv's
frame_type1(NULL, \%qv1, 1);
  sequence_end ( );
```

fig. 64

```
sub frame
{
$QVf  = 'frame' ;
%qv = ('delay_qv' = > [10000]);
%qp = ( );
compile_init (@_,\%qp, \%qv, $QVf);
      Delay('Delay_qv1');
compile_finit ( );
}
```

fig. 65


```
pDFN->DFNChangeQueueVariable
(
(char *) SymName,                    // variable name
(char *) sndBuf,                     // new value
BufSize                              // num bytes to write
  (ULONG *) & Debug                  // developer info
);
```

fig. 66

```
// load and run the event sequence
pDFNBeginSequenceNoMappingNoLog
      (snum,"d:\\HF.bin") ;
// assign data to be passed
sndBuf = 25000;
// change the queue variable
pDFN->DFNChange QueueVariable
(
  (char *) SymName,              // variable name
  (char *) sndBuf,               // new value
  (ULONG ) sizeof sndBuf         // num bytes to write
  (ULONG *) & debug              // developer info
);
```

fig. 67

```
sub frame_type1
{
 $HFfrm = 'frame_type1';
 %qv = ('delay_qv' = > [20000]);
 %qp = ( );
 $image_cmd  = [0x800000,0x0];
 compile_init (@_,\%qp, \%qv, $HFfrm);
   Send ( $image_cmd);
    Delay('delay_qv');
    LoopKF(2, 0xAAFF01);
   compile_finit( ) ;
}
```

fig. 68


112
337
Image Detector Subsystem
380
DFN Memory Unit
Physical Address List
DFN 304
Host Computer
114
Text
Physical Computer Memory
362
Mapped Virtual Memory
Mapped Virtual Memory
AGP Memory
Mapped Virtual Memory
Unmapped Virtual Memory
Mapped Virtual Memory
Unmapped Virtual Memory
Tester Virtual Address Space
338
High Res Display

fig. 69


732
User Process
732
User Process
730
User Mode
734
Operating System Kernel
314
DFN Device Driver
Kernel Mode
304
Detector Framing Node

fig. 71


PHYSICAL ADDRESS
512 MB
742
736
130 MB
128 MB (MAXMEM)
0 MB
Detector Images
Phys Addrs List
A
B
Operating System Kernel
Register Key
PhysicalMemory/ PhysicalMemorySize
738
740
PhysicalMemory/ PhysicalDFN WindowSize(2MB)
(Shared DFN Window)
PhysicalMemory/Maxmem
ResponseLogParameters/ BufferSize
734

fig. 72


Free Space
Detector Images
Frame 3
Frame 2
Sequence 2 (Current Sequence)
Frame 1
Frame 0
Frame 2
Sequence 1
Frame 1
Frame 0
a0, a1, a2, a3
A
B
MAXMEM
Operating System Kernel
Current Sequence Frame Address List
734

fig. 73